

1 C. EXECUTION

2
3 REMOVALS

- 4
5 1. Demolish concrete and/or masonry walls in small sections.
6 2. Locate demolition equipment throughout the structure and remove materials so as to not impose
7 excessive loads to supporting walls, floors or framing.
8 3. Remove existing walls, partitions, ceilings, finishes, and other materials where shown or required.
9 4. Remove existing mechanical and electrical items noted for removal.
10 5. Where walls are to be removed next to walls scheduled to remain, the walls shall be sawcut to provide a
11 straight edge.
12

13 The Contractor shall be responsible for providing all necessary temporary shoring and supports as required during
14 removal of existing walls, floors, and other structural items and until final structural replacement items are in place.
15 He shall be responsible for any damage to existing facilities which are scheduled to remain caused by his
16 demolition operations. The Government will not be responsible for any problems or accidents which occur
17 because of the Contractor's failure to thoroughly inspect the structure and review the Drawings of the existing
18 building before removing such items. A copy of the Government's Drawings of the existing building is available for
19 review at the office of the Government Construction Representative during construction of the project. These
20 Drawings may be helpful to the Contractor in determining the sequence or methods of removal for certain items.
21 The Contractor shall be responsible for verifying the accuracy of such existing Drawings before making decisions
22 regarding demolition based upon them.
23

24 Dispose of rubbish, debris and material resulting from demolition and removal operations to an offsite area within a
25 maximum of two weeks from the date of the removal from its original installation.
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57